

EURO 5

CANTER



mitsubishi FUSO TRUCK & BUS CORPORATION



800 ALHABTOOR
254228667
crm@alhabtoormotors.com



AL HABTOOR/MOTORS

The Canter Recipe for Success

وصفة كانتر للنجاح

Buying a new commercial vehicle is a long-term investment in the future of your company. So there's no room for compromises. When configuring your Canter, you can rely on a very simple recipe for success:

5 weight segments + 3 cab variants + 2 engine variants (96kw and 110kw) + 2 transmission types + 5 wheelbases + 1 universal frame hole pattern = the tailor-made solution for your company.

ان شراء مركبة يعد استثماراً طويلاً الأجل في مستقبل شركتك. لذلك فليس هنالك مجال للخلل المتوسطة. ان الوصفة البسيطة للنجاح تعتمد على 5 مواصفات لمركبة الكانتر الخاصة بك وهم:

5 لثقاسم للوزن + 3 أنواع مختلفة من الكابينات + نوعان مختلفان للمحرك (96 كيلوواط) + نوعان للنقل الحر + 5 أنواع من الإطارات + 1 نمط هيكل عالمي = الحل المعد خصيصاً لشركتك.



- Refined cab design combines rugged strength with meticulous attention to detail
- Body type variations to meet every business need
- Smooth driving, and easy to load and unload

- تصميم الكابينة يجمع ما بين الصلابة والمتانة مع إيلاء الاهتمام بأدق التفاصيل
- أنواع مختلفة من طراز الهيكل لتلبية جميع احتياجات العمل
- قيادة تمتاز بالسلاسة بالإضافة الى السهولة في التحميل والتفريغ

- Spacious cabin, loaded with features
- Clean, powerful, fuel-efficient engine
- Outstanding safety features and solid reliability

- كابينة فسيحة تحتوي على العديد من المميزات
- محرك نظيف وقوي واقتصادي في استهلاك الوقود
- خصائص سلامة ممتازة وموثوقية عالية

SPECIFICATIONS

TECHNICAL FEATURES

Model	FEB71EL4SAFC: E61	FEB71GL4SAFC: E63	FEB71GL4W AFC: E62	FEB91GL4SAFC: E63
Drive Type (Pay load)	4.2 Tons Single Cab	4.2 Tons Single Cab	4.0 Tons Double Cab	4.9 Tons Single Cab
Seating Capacity	Crew 3 (1+2)			
Dimension L x W x H (mm)	5,950 X 2,035 X 2,215	6,700 X 2,035 X 2,210	6,700 X 2,035 X 2,240	6,700 X 2,035 X 2,210
Wheel Base	3,400 mm	3,850 mm		

Kerb Weight (kg)	2,355	2,385	2,610	2,385
Gross Vehicle Weight (kg)	6,500			7,500

Maximum Speed (km/h)	126		120	
----------------------	-----	--	-----	--

Model	2998 cc, 4-Cylinder, EURO V
Type	4-Stroke Cycle, Water Cooled Direct Injection Diesel Engine
Max. Output	110 kW /3500 RPM
Max. Torque	370 Nm/1320 RPM

Transmission	5 Forward + 1 Reverse
--------------	-----------------------

Tire – Front	Single
Tire – Rear	Dual Rib Tires 215/75R17.5
Brake: Service	ABS + EBD
Parking Brake	■ (Standard)
Brake: Auxiliary	Exhaust Brake
Fuel Tank Capacity (L)	100
Electrical System – Battery	12V / 24V
Tool Set	■ (Standard)
Front Fog Lamp	■ (Standard)
Wheel Size	17.5 x 6-127-9t
6 Studs, 2 Pieces	■ (Standard)

Driver's Cab All Steel	■ (Standard)	—
Sun Visor		
Steering Ball & Nut Type with Hydraulic Power Booster Telescopic and Tilt Steering Column with Steering Lock		
Power Steering		
Power Windows		
Central Locking System		
Inside Rear View Mirror		
Air Bags – Driver & Assistant		
Fabric Seats		
Seatbelts for All		
Rear Under View Mirror		
Reverse Warning Buzzer		

AC	Including Heater and Defroster	Dual Air Conditioner, Including Heater and Defroster	Including Heater and Defroster
----	--------------------------------	--	--------------------------------



SPECIFICATIONS

TECHNICAL FEATURES			
Model	FECX1HL4SAFC: E66	FGB71EL6SAFC: E11	FGB71EL6WAFc: E12/E78/W53
Drive Type (Play load)	6.0 Tons Single Cab	(4x4) 3.2 Tons Single Cab	(4x4) 3.2 Tons Double Cab
Seating Capacity	Crew 3 (1+2)		Crew 7
Dimension L x W x H (mm)	7,255 X 2,145 X 2,215	5,950 X 2,035 X 2,485	5,950 X 2,035 X 2,505
Wheel Base	4,300 mm	3,415 mm	
Kerb Weight (kg)	2,410	2,825	2,825
Gross Vehicle Weight (kg)	8,550	6,000	
Maximum Speed (km/h)	119	124.1	
Model	2998 cc, 4-Cylinder, EURO V		
Type	4-Stroke Cycle, Water Cooled Direct Injection Diesel Engine		
Max. Output	110 kW /3500 RPM		
Max. Torque	370 Nm/1320 RPM		
Transmission	5 Forward + 1 Reverse		
Tire – Front	Single		
Tire – Rear	Dual Rib Tires 215/75R17.5		
Brake: Service	ABS + EBD		
Parking Brake	■ (Standard)		
Brake: Auxiliary	Exhaust Brake		
Fuel Tank Capacity (L)	100		
Electrical System – Battery	12V / 24V		
Tool Set	■ (Standard)		
Front Fog Lamp	■ (Standard)		
Wheel Size	17.5 x 6-127-9t		
6 Studs, 2 Pieces	■ (Standard)		
Driver’ s Cab All Steel	■ (Standard)	—	
Sun Visor			
Steering Ball & Nut Type with Hydraulic Power Booster Telescopic and Tilt Steering Column with Steering Lock			
Power Steering			
Power Windows			
Central Locking System			
Inside Rear View Mirror			
Air Bags – Driver & Assistant			
Fabric Seats			
Seatbelts for All			
Rear Under View Mirror	■ (Standard)	—	
Reverse Warning Buzzer			
AC	Including Heater and Defroster		



CANTER

Find us online



MITSUBISHI FUSO TRUCK & BUS CORPORATION



<https://habtoormotors.com/fusouae>

